



CRITICAL DIMENSION CHART

MARK	DESCRIPTION	FORMULA	DIM.
A	CLEAR OPENING	UP TO 32' *	-
B	POST HEIGHT	84"	-
C	NOMINAL GATE HEIGHT	UP TO 8' *	-
D	OVERALL GATE LENGTH	(A-14")/2	-
E	FABRIC HEIGHT	C-12"	-
F	ARM ATTACHMENT POINT (6' MAX.)	D/2	-
G	POST SPACING (BETWEEN)	E - 1'-0"	-

- NOTES:**
1. OPERATOR SUPPORT POST SIZE WILL VARY DEPENDING ON THE CLEAR OPENING WIDTH.
 2. BARB ARMS ARE OPTIONAL.
 3. GATE ELEVATION IS VIEWED FROM THE OUTSIDE OF THE SECURE AREA LOOKING IN.
 4. 50' STANDARD FROM CONTROL BOX TO POST.

ELEVATION

Scale: None

*CONTACT MANUFACTURER FOR LARGER SIZES.



2549 STATE ROUTE 40
GREENWICH, N.Y. 12834
PH:(800) 328-4283 - FX:(518) 692-9404

www.tymetal.com

TYM-4000-SR SECURITY GATE SYSTEM
(WITH DOUBLE HEAVY DUTY SWING GATE OPERATOR)

UP TO 7' NOMINAL GATE HEIGHT W/ STANDARD 80" OPERATOR